

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 960 930 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**01.12.1999 Bulletin 1999/48**

(51) Int Cl.<sup>6</sup>: **C10L 1/16, C10L 1/14,  
C10L 1/08**

(21) Application number: **99303770.4**

(22) Date of filing: **14.05.1999**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **15.05.1998 JP 15203398**

(71) Applicant: **TONEN CORPORATION**  
**Chiyoda-Ku, Tokyo 100 (JP)**

(72) Inventors:  
• **Nakajima, Isao, Corp. Res. & Dev. Lab.  
Iruma-gun, Saitama (JP)**

• **Hino, Takashi, Corp. Res. & Dev. Lab.  
Iruma-gun, Saitama (JP)**

(74) Representative: **Fletcher Watts, Susan J. et al**  
**ESSO Engineering (Europe) Limited,**  
**Patents and Licences,**  
**Mailpoint 72,**  
**Esso House,**  
**Ermyrn Way**  
**Leatherhead, Surrey KT22 8XE (GB)**

(54) **Diesel fuel oil composition**

(57) The present invention provides a diesel fuel oil composition comprising a base fuel which contains normal paraffin compounds having a carbon number of 20

or more at 4.0 wt% or less, has a specific carbon number distribution in the high-boiling normal paraffin compounds, contains sulfur at 0.05 wt% or less, and is incorporated with 0.01 to 0.1 wt% of a flow improver.

**EP 0 960 930 A1**

**Description**DETAILED DESCRIPTION OF THE PRESENT INVENTION5 FIELD OF INDUSTRIAL UTILIZATION

[0001] This invention relates to a new diesel fuel oil composition, more particularly the composition characterized by base fuel which contains a specific content of normal paraffin compounds having a carbon number of 20 or more, has a specific carbon number distribution in the high-boiling normal paraffin compounds, and is incorporated with a flow improver (FI).  
10

PRIOR ART

[0002] Diesel engines are widely used for various purposes, e.g., for driving automobiles, ships and construction machines, and are still spreading further. As a result, fuel for diesel engines is increasingly in demand, and becoming heavier to satisfy the increased demands, because straight-run diesel fuel oil is distilled deeper and/or blended with heavier fractions. This is accompanied by several problems, e.g., deteriorated fluidity at low temperature (i.e., increased pour point and/or cold flow plugging point). It is anticipated, therefore, that several engine troubles, e.g., plugging of fuel passage or fuel filter, may occur regionally in a normal temperature range at which the engine is operated in some districts.  
15  
20

[0003] Several measures against deteriorated fluidity of diesel fuel oils at low temperature have been proposed to provide fuel oils having adequate pour point and cold flow plugging point (CFPP) properties for temperature conditions, in particular in cold districts. These measures include limitation on end point of straight-run diesel oil, limitation on use of heavier fractions as the blending stocks, use of lighter blending stocks, and use of adequate additives, e.g., fluidity improver, including pour point depressant and FI, to improve e.g., fluidity improver, including pour point depressant and FI, to improve fluidity at low temperature. For example, Japanese Laid-open Patent application No. 8-157839 discloses fuel oil composition characterized by base fuel which contains normal paraffin compounds at 15 wt% or less, normal paraffin compounds having a carbon number of 20 or more at 1.2 wt% or less, and sulfur at 0.15 wt% or less, as the composition serviceable in cold districts, high in density, sufficiently low in pour point and allowing the engine to produce a high power.  
25  
30

[0004] Japanese Laid-open Patent application No. 7-331261 discloses a diesel fuel oil composition composed of diesel oil having an end point in a range from 320°C to 340°C, incorporated with 0.1 to 2.0 vol% of a fraction containing normal paraffin compounds having a carbon number of 26 to 31 and 100 to 600 ppm of an ethylene vinyl acetate-based additive to improve fluidity at low temperature. This composition is aimed at abatement of particulate emissions from a diesel engine and improvement of low-temperature fluidity, measured by CFPP.  
35

[0005] Limitation on end point of straight-run diesel oil and limitation on use of heavier fractions as the blending stocks to secure low-temperature fluidity of diesel fuel oils provide a good pour point, but are difficult to provide a good CFPP. Moreover, these approaches contribute little to increasing diesel fuel oil supplies. Blending diesel fuel oil with a lighter fraction decreases flash point and also decreases engine output. Use of an additive, such as pour point depressant or FI, involves some problems. For example a pour point depressant, although decreasing pour point, will not decrease CFPP. A FI, on the other hand, although generally decreasing pour point and CFPP, may not efficiently decrease CFPP, depending on type of stock for base fuel which constitutes diesel fuel oil or distillation properties of base fuel.  
40

[0006] It is an object of the present invention to provide a diesel fuel oil composition showing good CFPP by improving the prior-art techniques.  
45

DESCRIPTION OF THE INVENTION

[0007] It has been discovered that good CFPP can be secured when the base fuel satisfies the relationships of  $0 < A \leq 4.00$  (wt%) (wherein, A is content, based on all normal paraffin compounds present in the base fuel, of normal paraffin compounds having a carbon number of 20 or more), and  $0.04 \leq [B/C] \leq 0.40$  (wherein, B is content of normal paraffin compounds having a carbon number of  $n + 5$ , C is content of normal paraffin compounds having a carbon number of  $n$ ;  $[B/C]$  is average B/C ratio; and (n) is an integer when total content of normal paraffin compounds having a carbon number of (n) or more account for 3.0 wt% of total content of the normal paraffin compounds in the base fuel), and is incorporated with 0.01 to 0.10 wt% of a FI, reaching the present invention.  
50  
55

[0008] The present invention provides a diesel fuel oil composition characterized by base fuel satisfying the relationships  $0 < A \leq 4.00$  wt% (wherein A is content, based on all normal paraffin compounds present in the base fuel, of normal paraffin compounds having a carbon number of 20 or more) and  $0.04 \leq [B/C] \leq 0.40$ , and being incorporated

with 0.01 to 0.10 wt% of a FI.

**[0009]** The present invention, relating to the above diesel fuel oil composition, includes the following preferred embodiments:

- (1) the diesel fuel oil composition, wherein a [B/C] ratio is 0.07 to 0.20,
- (2) the diesel fuel oil composition, wherein content of the FI is 0.03 to 0.07 wt%, and
- (3) the diesel fuel oil composition of one of (1), wherein the content of the FI is 0.03 to 0.07 wt%.

**[0010]** The present invention is described below in detail. The diesel fuel oil composition of the present invention is characterized by base fuel which contains a specific content of A, has a [B/C] ratio in a specific range, and is incorporated with 0.01 to 0.10 wt% of a FI.

**[0011]** The base fuel for the present invention mainly comprises a mineral oil, having a flash point of 40°C or higher and 90% distillation temperature of 360°C or lower. The mineral oil for the present invention is a petroleum fraction, including a petroleum fraction obtained by atmospheric distillation of crude oil, and petroleum fraction obtained by atmospheric or vacuum distillation of crude oil and refined by an adequate process, e.g., hydrogenation, hydrocracking, catalytic cracking and a combination thereof. These petroleum fractions can be used individually or in combination. The base fuel component other than petroleum fraction includes vegetable oil, e.g., soybean, coconut and rape oil, and animal oil, e.g., whale and fish oil.

**[0012]** The diesel fuel oil composition of the present invention satisfies the relationship  $0 < A \leq 4.00$  (wt%) (wherein, A is content, based on all normal paraffin compounds present in the base fuel, of normal paraffin compounds having a carbon number of 20 or more). A diesel fuel oil composition may cause engine troubles, e.g., plugging of the fuel passage or fuel filter, when its base fuel contains normal paraffin compounds having a carbon number of 20 or more (hereinafter referred to as (n-C<sub>20</sub>+)) at above 4.00 wt%, as ambient temperature decreases, because the normal paraffin compounds will separate out.

**[0013]** The diesel fuel oil composition of the present invention also satisfies the relationship  $0.04 \leq [B/C] \leq 0.40$  (wherein, B is content of normal paraffin compounds having a carbon number of n + 5, C is content of normal paraffin compounds having a carbon number of n; [B/C] is average B/C ratio; and (n) is an integer when total content of normal paraffin compounds having a carbon number of (n) or more account for 3.0 wt% of total content of the normal paraffin compounds in the base fuel). Assuming that the normal paraffin compounds having a carbon number of 20 or more accounts for 3.0 wt% of the total normal paraffin components of the base fuel, the average of the  $(n-C_{25})/(n-C_{20})$ ,  $(n-C_{26})/(n-C_{21})$ ,  $(n-C_{27})/(n-C_{22})$ , ..., ratios consecutively calculated is in a range from 0.04 to 0.40, inclusive. When [B/C] is below 0.04, some of the normal paraffin compounds in the base fuel may separate out as large planar crystals as ambient temperature decreases, even when the relationship  $0 < A \leq 4.00$  (wt%) is satisfied, to easily cause plugging of the fuel filter. In other words, such a base fuel has an excessively high CFPP. The similar troubles will occur, when [B/C] exceeds 0.40. [B/C] is preferably in a range from 0.07 to 0.20, inclusive. The base fuel shows a good CFPP, even when ambient temperature decreases, when it satisfies the relationships  $0 < A \leq 4.00$  (wt%) and  $0.04 \leq [B/C] \leq 0.40$ , preferably  $0.07 \leq [B/C] \leq 0.20$ .

**[0014]** The component (n-C<sub>20</sub>+) of the base fuel for the present invention can be selected from adequate petroleum fractions of different normal paraffin content. These petroleum fractions include petroleum fractions obtained by atmospheric distillation of crudes of different normal paraffin content, and petroleum fractions obtained by atmospheric or vacuum distillation of crude(s) and refined by an adequate process, e.g., solvent dewaxing and catalytic dewaxing. [B/C] of the base fuel can be adjusted by controlling extent of rectification for the distillation operation. [B/C] increases as extent of rectification decreases. The above petroleum fractions can be used individually or in combination to adjust the component (n-C<sub>20</sub>+) content and [B/C] levels for the base fuel for the present invention.

**[0015]** The FI useful for the present invention can be selected from the known ones. These include ethylene glycol ester-based compounds, ethylene-vinyl acetate copolymers, ethylene alkylacrylate-based copolymers, chlorinated polyethylene, polyalkyl acrylate, and alkenyl succinamide-based compounds. A FI dosage below 0.01 wt% may not satisfactorily decrease CFPP, and above 0.1 wt% is not economical, because CFPP will not decrease as much as increased dosage. The preferable FI dosage is 0.03 to 0.07 wt%. The above FI's may be used individually or in combination.

**[0016]** The diesel fuel oil composition of the present invention may be incorporated with other known additives for fuel oil, so long as its performance is not damaged. These additives include cetane improver, oxidation inhibitor, metal passivator, detergent, corrosion inhibitor, pour point depressant, de-icer, bactericide, combustion promoter, antistatic agent, lubricity improver, and coloring agent. A general dosage of the additive is 0.1 to 0.5 wt% in the case of pour point depressant, although not limited to this level. One or more of these additives may be used for the present invention, as required.

**[0017]** The diesel fuel oil composition of the present invention may be also incorporated with one or more types of oxygenated compounds so long as its performance is not damaged. These compounds include alcohols, e.g., methanol, ethanol, isopropanol, n-butanol, isobutanol, tert-butanol, amyl alcohol, isoamyl alcohol, n-octanol, 2-ethyl hexanol, n-heptyl alcohol, tridecyl alcohol, cyclohexanol and methyl cyclohexanol; and methyl tert-butyl ether, ethyl tert-butyl ether; dialkyl phthalate, diethylene glycol dimethyl ether and ethyl maleate. A general dosage of the oxygenated compound, e.g., alcohol compound, is 3 to 15 wt%, although not limited to this level.

**[0018]** The present invention is described in more detail by the embodiments presented below, which by no means limit the present invention. The following base fuels, FI's and lubricity improver were used for Examples and Comparative Examples. Measurements of CFPP and (n-C<sub>20</sub>+) are also described.

(1) Base Fuel

**[0019]** A total of 17 types of base fuels were used. Their properties are given in Tables 1 and 2.

TABLE I

Base Oil								
	A	B	C	D	E	F	G	H
Density (g/cm <sup>3</sup> )	0.8369	0.8338	0.8248	0.8461	0.8262	0.8457	0.8370	0.8365
Flash Point (°C)	70	68	69	69	71	75	73	75
Distillation (°C)								
Initial boiling point	176.0	182.0	161.5	224.0	180.0	215.0	208.0	216.0
10%	222.5	220.5	212.5	260.0	221.5	257.0	248.0	254.0
50%	287.5	279.0	279.0	294.0	274.5	292.0	287.0	287.0
90%	346.0	345.0	342.5	340.0	328.5	336.0	334.0	330.0
End point	376.5	377.0	374.0	365.0	357.0	357.0	357.0	353.0
Cloud Point (°C)	- 4	- 3	- 4	- 2	- 2	0	1	1
CFPP (°C)	- 5	- 4	- 4	- 3	- 3	- 2	0	- 2
Pour point (°C)	- 7.5	- 5	- 7.5	- 2.5	- 2.5	- 2.5	0	0
(n-C <sub>20</sub> +) (wt%)	2.78	3.03	2.82	3.05	4.46	3.30	3.45	3.80

TABLE 2

Base Oil										
	I	J	K	L	M	N	O	P	Q	
Density (g/cm <sup>3</sup> )	0.8377	0.8350	0.8369	0.8403	0.8425	0.8139	0.8255	0.8355	0.8348	
Flash Point (°C)	70	68	69	69	71	75	73	75	72	
Distillation (°C)										
Initial boiling point	171.0	175.0	172.0	146.5	139.0	194.5	167.0	170.0	172.5	
10%	230.5	228.5	230.0	218.0	222.0	225.0	228.0	230.0	232.5	
50%	280.0	278.5	279.5	276.0	280.0	265.5	273.0	280.0	281.5	
90%	343.0	345.5	344.0	334.0	334.5	312.0	324.0	346.0	350.0	
End Point	372.0	376.0	373.0	361.5	361.0	329.0	346.0	376.0	375.0	
Cloud Point (°C)	-2	-2	-2	-1	-1	-5	-4	-1	0	
CFPP (°C)	-3	-3	-3	-3	-3	-6	-5	-2	-2	
Pour Point (°C)	-5	-5	-5	-5	-5	-7.5	-5	-2.5	-2.5	
(n-C <sub>20</sub> +) (wt%)	1.06	0.92	1.02	3.61	3.92	0.90	1.57	3.35	4.72	

(2) FI

[0020] An ethylene glycol ester-based FI(ECA9911, produced by Exxon Chemical) and ethylene-vinyl acetate-based FI (PF240, produced by Exxon Chemical) were used.

(3) Measurement of CFPP

[0021] CFPP was measured as per JIS K-2288.

(4) Measurement of n-C<sub>20</sub>+

[0022] Content of an individual normal paraffin compound in each base fuel was measured by gas chromatography using an analyzer (GC-6AM, produced by Shimadzu), where each sample was passed through a capillary column (inner diameter: 0.25 mm, length: 15 m, impregnated with methyl silicon to a thickness of 0.1 μm) at 50°C to 350°C. n-C<sub>20</sub>+ is defined as total content of normal paraffin compounds having a carbon number of 20 or more.

[0023] The base fuel samples shown in Tables 1 and 2 were used to prepare the fuel oil samples shown in Tables 3 and 4, to measure CFPP levels and properties of the base fuels. The results are given in Table 3 for Examples and Table 4 for Comparative Examples.

[0024] [B/C] was determined by the following procedure. Content of an individual normal paraffin compound in each base fuel was measured by gas chromatography. Content of the normal paraffin compound having the largest carbon number, and contents of the normal paraffin compounds having smaller carbon numbers are calculated consecutively, where (n) is defined as the integer when total content of normal paraffin compounds having a carbon number of (n) or more account for 3.0 wt% of total content of the normal paraffin compounds in the base fuel. Next, (content of normal paraffin compounds having a carbon number of (n + 5))/(content of normal paraffin compounds having a carbon number of (n)) ratios are calculated, and the average is taken as [B/C]. The same gas chromatography as that for measurement of (n-C<sub>20</sub>+) was used.

TABLE 3

	EXAMPLES								
	1	2	3	4	5	6	7	8	9
Fuel oil compositions (wt%)									
(a) Base fuel A	99.96								
(b) Base fuel B		99.96							
(c) Base fuel C			99.96						
(d) Base fuel D				99.96					
(e) Base fuel I					99.98				
(f) Base fuel J						99.98			
(g) Base fuel K							99.98		
(h) Base fuel L								99.98	
(i) Base fuel M									99.98
(j) Dosage of FI									
• ECA9911	0.04	0.04	0.04	0.04	--	--	--	--	--
• PF240	--	--	--	--	0.02	0.02	0.02	0.02	0.02



TABLE 3 (continued)

	EXAMPLES								
	1	2	3	4	5	6	7	8	9
Properties of base fuel (n-Paraffins)									
(a) (n-C <sub>20</sub> +) (wt%)	2.78	3.03	2.82	3.05	1.06	0.92	1.02	3.61	3.92
(b) [B/C]	0.092	0.089	0.089	0.054	0.354	0.154	0.248	0.086	0.100
CFPP (°C)									
(a) Base fuel (incorporated with no FI)	- 5	- 4	- 4	- 3	- 3	- 3	- 3	- 3	- 3
(b) Fuel oil (incorporated with an FI)	- 16	- 13	- 14	- 9	- 12	- 12	- 12	- 11	- 9
(c) Difference in CFPP [(a)-(b)]	11	9	10	6	9	9	9	8	6

TABLE 4

	COMPARATIVE EXAMPLES							
	1	2	3	4	5	6	7	8
Fuel oil compositions (wt%)								
(a) Base fuel E	99.96							
(b) Base fuel F		99.96						
(c) Base fuel G			99.96					
(d) Base fuel H				100				
(e) Base fuel N					99.98			
(f) Base fuel O						99.98		
(g) Base fuel P							99.98	
(h) Base fuel Q								99.98
(i) Dosage of FI								
• ECA9911	0.04	0.04	0.04	--	--	--	--	--
• PF240	--	--	--	--	0.02	0.02	0.02	0.02

TABLE 4 (continued)

	COMPARATIVE EXAMPLES							
	1	2	3	4	5	6	7	8
Properties of base fuel (n-Paraffins)								
(a) (n-C <sub>20</sub> +) (wt%)	4.46	3.30	3.45	3.80	0.90	1.57	3.35	4.72
(b) [B/C]	0.027	0.035	0.434	0.045	0	0	0.460	0.32
CFPP (°C)								
(a) Base fuel (incorporated with no FI)	- 3	- 2	0	- 2	- 6	- 5	- 2	- 2
(b) Fuel oil (incorporated with an FI)	- 4	- 3	0	- 2	- 7	- 6	- 3	- 3
(c) Difference in CFPP [(a)-(b)]	1	1	0	0	1	1	1	1

[0025] As shown in Table 3, diesel fuel oil exhibits a notably low CFPP of -9 to -16°C, when it comprises a base fuel which contains a specific content of the component (n-C<sub>20+</sub>), has a [B/C] value in a specific range, and is incorporated with an adequate FI. Its CFPP is significantly lower than that of the base fuel by 6 to 11°C. By contrast, the samples prepared by Comparative Examples, which do not satisfy the relationship with respect to (n-C<sub>20+</sub>) or [B/C], has a CFPP value high and virtually unchanged (or decreased by 0 or 1°C) from that of the base fuel, even when incorporated with a FI, as shown in Table 4. It is also found that diesel fuel oil shows insufficient CFPP without FI, even when its base fuel contains a specific content of (n-C<sub>20+</sub>) and has a [B/C] value in a specific range. It is therefore essential for a diesel fuel oil composition to comprise a base fuel which contains a specific content of (n-C<sub>20+</sub>), has a [B/C] value in a specific range, and is incorporated with an adequate FI, in order to exhibit good CFPP.

[0026] As described above in detail and concretely, the present invention provides a diesel fuel oil composition which exhibits good CFPP by incorporating a base fuel satisfying the relationships  $0 < (n-C_{20+}) \leq 4.00$  (wt%) and  $0.04 \leq [B/C] \leq 0.40$  with an adequate FI.

## Claims

1. A diesel fuel oil composition comprising a base fuel which satisfies the following relationships (1) and (2), and is incorporated with 0.01 to 0.10 wt% of a flow improver:

$$(a) \ 0 < A \leq 4.00 \quad (1)$$

wherein, A is content, based on all normal paraffin compounds present in the base fuel, of normal paraffin compounds having a carbon number of 20 or more (wt%), and

$$(b) \ 0.04 \leq [B/C] \leq 0.40 \quad (2)$$

wherein, B is content of normal paraffin compounds having a carbon number of n + 5 (wt%), C is content of normal paraffin compounds having a carbon number of n (wt%); [B/C] is average B/C ratio, and (n) is an integer when total content of normal paraffin compounds having a carbon number of (n) or more account for 3.0 wt% of total content of the normal paraffin compounds in the base fuel.

2. The diesel fuel oil composition of claim 1 wherein the [B/C] ratio is 0.07 to 0.20.
3. The diesel fuel oil composition of claim 1 or 2 wherein the flow improver content is in the range of 0.03 to 0.07 wt%.



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 3770

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
P,X	DATABASE WPI Section Ch, Week 9921 Derwent Publications Ltd., London, GB; Class E19, AN 99-248626 XP002113916 & JP 11 071586 A (TONEN CORP), 16 March 1999 (1999-03-16) * abstract *	1-3	C10L1/16 C10L1/14 C10L1/08
D,A	--- PATENT ABSTRACTS OF JAPAN vol. 096, no. 010, 31 October 1996 (1996-10-31) & JP 08 157839 A (IDEMITSU KOSAN CO LTD), 18 June 1996 (1996-06-18) * abstract *	1-3	
A	--- EP 0 301 837 A (SUMITOMO CHEM. COMP.) 1 February 1989 (1989-02-01) * the whole document *	1-3	
A	--- FR 2 249 945 A (EXXON RES. AND ENG.) 30 May 1975 (1975-05-30) * the whole document *	1-3	TECHNICAL FIELDS SEARCHED (Int.Cl.6) C10L
A	--- EP 0 255 345 A (EXXON CHEM. PAT.) 3 February 1988 (1988-02-03) * the whole document *	1-3	
A	--- GB 1 264 638 A (ESSO RES. AND ENG.) 23 February 1972 (1972-02-23) * the whole document *	1-3	
A	--- GB 1 264 684 A (ESSO RES. AND ENG.) 23 February 1972 (1972-02-23) * the whole document *	1-3	
		-/---	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 1 September 1999	Examiner De La Morinerie, B
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03/02 (P4/C01)



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 3770

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	GB 1 266 037 A (ESSO RES. AND ENG.) 8 March 1972 (1972-03-08) * the whole document *	1-3	
A	EP 0 308 176 A (EXXON CHEM. PAT.) 22 March 1989 (1989-03-22) * the whole document *	1-3	
A	US 4 210 424 A (FELDMAN ET AL.) 1 July 1980 (1980-07-01) * the whole document *	1-3	
D,A	PATENT ABSTRACTS OF JAPAN vol. 096, no. 004, 30 April 1996 (1996-04-30) & JP 07 331261 A (MITSUBISHI OIL CO LTD), 19 December 1995 (1995-12-19) * abstract *	1-3	
A	PATENT ABSTRACTS OF JAPAN vol. 007, no. 061 (C-156), 15 March 1983 (1983-03-15) & JP 57 207696 A (NIHON SEKIYU SEISEI KK), 20 December 1982 (1982-12-20) * abstract *	1-3	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>1 September 1999</b>	Examiner <b>De La Morinerie, B</b>
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P/4C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 3770

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-09-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 11071586 A	16-03-1999	NONE	
JP 08157839 A	18-06-1996	NONE	
EP 301837 A	01-02-1989	CA 1339640 A	27-01-1998
		DE 3876165 A	07-01-1993
		DE 3876165 T	10-02-1994
		JP 1103698 A	20-04-1989
		JP 4059356 B	22-09-1992
		JP 1103699 A	20-04-1989
		JP 4059357 B	22-09-1992
		JP 2714747 B	16-02-1998
		JP 6340885 A	13-12-1994
		JP 2714748 B	16-02-1998
		JP 6192666 A	12-07-1994
FR 2249945 A	30-05-1975	BE 821656 A	30-04-1975
		CA 1021158 A	22-11-1977
		DE 2450793 A	07-05-1975
		GB 1469016 A	30-03-1977
		IT 1025309 B	10-08-1978
		NL 7414240 A,B,	02-05-1975
EP 255345 A	03-02-1988	CN 1020631 B	12-05-1993
		DE 3782773 A	07-01-1993
		ES 2052569 T	16-07-1994
		IN 168192 A	16-02-1991
		IN 168378 A	23-03-1991
		JP 2541993 B	09-10-1996
		JP 63108096 A	12-05-1988
		KR 9514389 B	27-11-1995
GB 1264638 A	23-02-1972	US 3832150 A	27-08-1974
GB 1264684 A	23-02-1972	US 3640691 A	08-02-1972
GB 1266037 A	08-03-1972	US 3620696 A	16-11-1971
EP 308176 A	22-03-1989	AU 2236588 A	23-03-1989
		CN 1032184 A	05-04-1989
		JP 1158096 A	21-06-1989
US 4210424 A	01-07-1980	CA 1124519 A	01-06-1982
JP 07331261 A	19-12-1995	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 3770

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-09-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 57207696 A	20-12-1982	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82